




PCT/GB 2004 / 0 0 1 6 2 0



INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ



I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

**PRIORITY  
DOCUMENT**

SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

Signed

*Ansrews*

Dated

30 April 2004

BEST AVAILABLE COPY



1177  
15APR03 1800440-1 810464  
P01/7700 0-00-0308682.4

# Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

THE PATENT OFFICE  
B

15 APR 2003

NEWPORT

The Patent Office

Cardiff Road  
Newport  
South Wales  
NP10 8QQ

1. Your reference

PK1

2. Patent application number

(The Patent Office will fill in this part)

0308682.4

15 APR 2003

3. Full name, address and postcode of the or of each applicant (underline all surnames)

PETER KINSLER  
40 PARK ROAD, ABINGDON  
OX14 1DS

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

861157600

4. Title of the invention

THERMOMETER

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

40 PARK ROAD, ABINGDON  
OX14 1DS

Patents ADP number (if you know it)

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number  
(if you know it)

Date of filing  
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing  
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

No

- a) any applicant named in part 3 is not an inventor, or
  - b) there is an inventor who is not named as an applicant, or
  - c) any named applicant is a corporate body.
- See note (d))

# Patents Form 1/77

- 9 Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form 0

Description 16

Claim(s) 5

Abstract 1

Drawing(s) 5

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent. (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11. I/we request the grant of a patent on the basis of this application.

Signature P. Kinsler Date 2.4.03

12. Name and daytime telephone number of person to contact in the United Kingdom PETER KINSLER 01235 528232

## Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

## Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

# THERMOMETER

The present invention relates to the field of thermometers for measuring the temperature of the liquid contents of containers, particularly bottled liquids, such as wine.

Various types of thermometers are known in the prior art to measure the temperature of liquids, such as wine, directly, and display the result in various ways to facilitate reading temperature ranges, or optimal temperatures for different types of liquid. Examples are US 3,124,003, and US 4,104,916.

Although thermometers of the type described exist in the prior art, they possess a number of disadvantages undesirable in such devices. For instance, in measuring wine temperature the bottle would be opened just prior to serving to insert a thermometer into the wine thus risking contamination.

Wine connoisseurs know that the temperature of wine can make a considerable difference in taste and enjoyment and some vineyards are responding by listing the correct temperature on new labels. The importance of temperature of service is highlighted by the internationally -acclaimed wine expert Jancis Robinson in her book "Jancis Robinson's Wine Course" [ISBN: 1-85613-360-5] where she states "It is impossible to overestimate the effect of serving temperatures on how a wine will taste." Serving wine too cold reduces its aroma and flavour, and highlights any bitterness. Serving the wine too warm can make the flavours unpleasantly dull and flat and the wine seem harshly alcoholic. Any wine is best drunk within a temperature range of 2-3 °C. For example, very good Burgundy reds should be drunk at 15-16 °C, whereas very good Bordeaux reds require 17-18 °C. Optimal serving temperatures for wines are well known to the skilled person.

The process of withdrawing the cork at the time of serving and immersing a conventional thermometer into the wine to check its temperature is unsatisfactory, because if it is determined that the wine is not at the correct temperature, it is too late to compensate by heating or cooling the bottle.

Even if there is time for further iterations of heating or cooling the bottle and measuring the temperature to establish whether the wine is at the correct serving temperature, each time the temperature of the wine is measured, the bottle must be opened, the thermometer stem must be inserted to measure the temperature of the wine, and the bottle must be re-closed after the temperature measurement. It is not only inconvenient, but time-consuming to repeat this temperature-measuring sequence several times for a single bottle of wine. In addition, if this is done for an effervescent wine, such as champagne, it is even more troublesome, as several iterations of temperature measurement could result in the loss of effervescence when the wine is eventually served.

It would be advantageous to use a means of measuring liquid (particularly wine) temperature without opening the container first.

US 3,864,976 discloses a liquid crystal strip or band thermometer that may be attached to the side of a bottle with an elastomeric strip. US 4,538,926 discloses such a wine thermometer with a single liquid crystal composition that changes colour with temperature and a comparison band with which the colour can be compared. A symbol in the comparison band indicates the exact temperature for serving the wine in the bottle to which the device is attached. US 5,738,442 similarly pertains to thermometers for the measurement of wine temperature just prior to serving.

Using the liquid crystal technology above, the patch that constitutes the wine thermometer must be tightly attached adhesively to the side of the bottle exterior. Although the temperature inside the bottle can be roughly estimated without disturbing the wine, such patches can be unsightly on the bottle, and may be difficult to remove neatly.

WO 88/03512 discloses a contact-type thermometer for the side of the bottle. Contact-type thermometers are known, such as the Minimum Surface Thermometer manufactured by Testo. However these thermometers (and the patch thermometer) suffer from the disadvantage of having to remove the bottle from the fridge or

incubator to test the temperature of the liquid contents. Even if the temperature could be observed within the fridge or incubator with these methods, the accuracy of the thermometer can be significantly affected by being exposed not only to the container surface temperature, but also to the extreme ambient temperature of the fridge or  
5. incubator.

The present invention aims to alleviate the above problems by presenting a device that can measure the temperature of the contents of a container such as a wine bottle without disturbing the contents, but which can constantly monitor the  
10 temperature of the contents and signal the occurrence of the desired temperature of the container contents without having to remove the container from the fridge or incubator, and wherein the thermometer accuracy is not significantly affected by the extreme temperatures of the fridge or incubator.

15 The inventor has found that for containers with concave bases (such as wine bottles which typically have a conical or generally frusto-conical space in their base), the space in the base can be advantageously used to estimate the temperature of the liquid contents of the container. Such concave bases have a large surface area projecting into the liquid which allows a good thermal exchange between the liquid  
20 and the air space enclosed in the base of the container.

Thus according to the invention there is provided a device for externally estimating the temperature of the liquid contents of a (preferably sealed) container (particularly glass containers such as wine bottles) with a concave base, comprising a  
25 support means with at least one contacting portion for contacting the perimeter of the base of said container, a temperature probe which is positioned within the support means such that in use the probe may measure the temperature within the space enclosed by the concave base of the container and the support means, and a suitable system for displaying the estimated temperature of the liquid contents within the  
30 container (without the container having to be opened beforehand).

By "externally" it is meant that a temperature is measured outside the container. By "estimating" it is meant that the techniques of this invention are capable

of providing a temperature measurement which is a good approximation of the temperature of the internal liquid contents of the container (preferably within 1-2 °C, most preferably within 1 °C). By "concave base" it is meant that the container has a base which is internalised back into the container, thus an air pocket or cavity or space is present between the container's external surface and the plane perpendicular to the rim of the base of the container (into which the temperature probe of the invention may be placed). The concave base is typically a dome or cone or generally frustro-cone shape – as for wine bottles. Typically, the extent to which the base is internalised is 0.5-4 cm from the plane perpendicular to the rim of the base of the container (which is the case for most wine bottles – one of the shallowest cavities being a German Riesling bottle, and one of the deepest the Condrieu bottle from the Northern Rhône).

It is not essential that the perimeter of the base is thermally sealed by the contacting portion of the support means. If the container's contents are being cooled in the device placed in a fridge and the temperature probe is projected towards the top of the concave space (and the container is in a substantially vertical position) the probe will measure the temperature of the less dense air (warmed by the contents of the container) trapped in the concave space which will reflect the temperature of the liquid contents.

It is, however, preferred that the contacting portion of the support means is capable of contacting the entire perimeter of the base of the container such that the space between concave base of the container and the support means is enclosed such that it is thermally insulated from the ambient temperature outside the space, for instance that of the fridge, freezer or incubator into which the device may be placed.

Preferably, the contacting portion of the support means is made of a thermally insulating, deformable material such as rubber. It is also preferable that the support means (or at least the portion of it defining the enclosed space in the base of the container) is also made of thermally insulating material. In one embodiment, the contacting portion may be of a wide enough diameter to accommodate (make contact with the base rim) all various standard size containers or bottles. In addition, it is

preferred that the contacting portion forms a raised ridge projecting from the support means such that, when a container is placed upon it, it may deform around and make contact with any uneven surface on the perimeter of the base of the container. For instance, in a further embodiment the contacting portion may form an O-ring on the surface of the support means for containers with round bases, such as wine bottles. Wine bottles frequently have uneven gripping raised surfaces on their base, and such a contacting portion allows the deformable material to contact the whole perimeter of the base for good thermal insulation of the enclosed base space. Most preferably, the device can have 2 or more (e.g. 3, 4, or 5) concentric contacting portions suitable for contacting base perimeters of various sizes of container (see for example Diagrams 2 and 3). Again, for wine bottles, various concentric O-rings can be of a diameter to accommodate the various diameters of wine bottles (e.g. one small enough for half bottles of wine, one, two or three for various standard size wine bottles (e.g. Alsace, Burgundy and Bordeaux), and one to fit larger based wine bottles such as champagne bottles).

Preferably the support means of the device should also comprise a guide portion for guiding the placement of the base of the container onto the temperature probe and/or the contacting portion of the support means. For wine bottles this could constitute a generally cylindrical sleeve into which a wine bottle can be placed so that it will come into contact with the contacting portion and/or be optimally placed for the temperature probe to estimate the temperature of the contents of the bottle through its base space. Such a cylindrical sleeve (or guide portions in general) may be expandable to accommodate differently sized bottles (or containers) – such expansion preferably being concentric to the contacting portion of the support means. A cylindrical sleeve (or guide portions in general), for example, may be longitudinally divided in two halves which are resiliently biased towards each other. The cylindrical sleeve (or guide portions in general) is preferably slightly flared where the bottle enters the device in order to facilitate the expansion of the guide means. Alternatively the guide means could accommodate the neck of a container – such as a bottle.

The temperature probe can constitute any convenient means of measuring the temperature within the concave space. Preferably, the device has an electronic



temperature probe which is connected to suitable electronics for measuring and displaying, in use, the approximate temperature of the liquid contents of the container.

An electronic temperature probe can be any known device for instance a resistance thermometer, thermistor and preferably a thermocouple. Thermocouples are well known in the art, and typically comprise a first and a second metal (preferably copper and constantan, or Nickel and Nickel/Chromium alloy respectively). One junction of the metals is present in the base space of the container in use, and the other junction of the metals in the circuit is typically placed at a reference temperature (for instance a zero degree Celsius box found in many fridges). The voltage difference resulting from the two junctions at different temperatures is readily converted electronically to give the temperature reading at the base of the container which is conveniently shown on the display of the device. Display electronics can also employ several other features such as an alarm function for alerting the user when the desired temperature has been reached. There may also be a programmable function for entering the type of contents enclosed in the container which is associated in the memory with a particular serving temperature at which an alarm may operate or sound. For instance ideal serving temperatures of various types of wine can be entered into the memory of the device which can be selected by the user of the device so that the alarm can indicate optimal serving temperature has been reached without the user having to know themselves what this temperature is. The display can also show when the temperature of the contents are above or below the optimal range of temperature for the contents. In addition, using the rate of temperature drop or increase in the liquid contents of the container, the electronics could work out an approximate time for the contents to reach the desired temperature which could provide useful information for the user.

Typically the temperature measured in the concave space is a good approximation of the temperature of the liquid contents of the container (usually within 1-2 degrees Celsius, most preferably within 1 degree Celsius). Preferably the device of the invention is activated by means of a pressure switch either within the support means or the temperature probe when a bottle is placed on the device.

In one embodiment the device has a temperature probe which in use projects from the support means into the space enclosed by the concave base of the container

and the support means, preferably through an elongate projecting means. Preferably the elongate projecting means is positioned such that, in use, it projects the temperature probe towards the centre of the concave base of the container (or towards the top of the space enclosed within the concave base). Most preferably, the temperature probe is positioned such that in use it is in thermal contact with the surface of the concave base of the container. This has the advantage of using both the air temperature in the concave space and the contact temperature of the container (at a point which is protruding into the container's contents) for estimating the internal content temperature. Ideally the temperature probe would be in contact with the container at the top of the concave space (for instance at the apex of the cone or frustro-cone of the base of a wine bottle). The inventor has found that for wine bottles the apex is the most advantageous point to estimate the internal content temperature.

In an alternative (less preferred) embodiment, the device need not have support means with a contacting portion, and may comprise merely a temperature probe which, in use, projects from the device through an elongate projecting means within the space in the concave base of the container (and is preferably positioned such that, in use, it projects the temperature probe towards the centre of the concave base of the container) and support means (which need not contact the perimeter of the base of the container) for holding the container in position for the temperature measurement to take place. The container may rest on a substantially rigid temperature probe/elongate projection means for support, or the support means could retain the container in place either at the top, side or bottom of the container maintaining the temperature probe either in thermal contact with the concave base of the container, or simply extending towards the top of the cavity space. Preferably the container is retained in a substantially vertical position. It is therefore not essential (though again preferred) in this embodiment that the base cavity is thermally insulated from the ambient temperature of the fridge or incubator into which the device is placed. For instance, if the container's contents are being cooled in the device placed in a fridge and the temperature probe is projected towards the top of the concave space (and the container is in a substantially vertical position) the device will measure the temperature of the less dense air warmed by the contents of the container enclosed in the concave space which will reflect the temperature of the liquid contents.

Depending on the shape of the centre of the concave base of the container, the temperature probe may or may not be of the correct size to contact the container if it is extended in use to the top of the concave space. In a preferred embodiment, therefore, the temperature probe in use is in thermal contact with the surface of the concave base of the container through at least one flexible extension made of a material with good thermal conductivity which extends laterally from (and therefore in thermal contact with) the temperature probe. These flexible extensions are typically flat sheets of metal such as phosphor bronze or copper which can contact a portion of the internal concave area (preferably towards the centre or apex) of the base of the container. This has the advantage of making the thermal transfer between the concave base of the container (protruding into the liquid contents of the container) and the temperature probe particularly efficient. If the temperature probe is a thermocouple, the extensions should be ideally made of one of the metals forming the thermocouple to which they are connected (preferably copper). Most preferably the flexible extension is made of a resilient sheet of metal. If such a sheet extends laterally (or radially or transversely) from the temperature probe, the concave base of the container when placed on the temperature probe will tend to bend the extension into a shape with good thermal contact with the concave base; when removed from the device the extension should ideally restore itself to its original shape. Preferably there should be more than 1 (e.g. 2, 3 or 4) such extensions extending symmetrically from the temperature probe. See Diagrams 1, 2, 3 for examples of temperature probes with such extensions. In addition to extensions being applied to thermocouple temperature probes, the same idea may also be applied to resistance thermometer or thermistor-based temperature probes. See for example Diagram 5 showing such an extension principle for a resistance thermometer probe which leads to an increase in the sensitivity of the probe due to the increased length of wire. In some circumstances a resistance thermometer or a thermistor-based thermometer may be more readily used than a thermocouple as a reference temperature is not required (although resistance/thermistor thermometers need to be calibrated before being fitted to a device).

Preferably the elongate projecting means is longitudinally compressible by application of the container to the device. This allows the temperature probe to be in thermal contact with the container regardless of the depth of the cavity of the container used. The elongate projecting means may be capable of compressing to the level of the exterior surface of the support means which, in use, defines the space enclosed by the concave base of the container and the support means – that is, the compressed elongate projecting means might sit in a pocket built into the surface of the support means. In a preferred embodiment the elongate projecting means is telescopically arranged.

The compressed elongate projecting means may be compressed by application of the container to the device, and, once the container is removed, the elongate projection means is manually extended for the next container to be measured. Most preferably, the device of the invention has elongate projecting means that is resiliently biased towards the concave base of the container. In such case the elongate projecting means can take the form of a coiled spring (see for example Diagram 1) which is most preferably supported or maintained in an upright orientation through a spring guide means. The elongate projecting means preferably is a resiliently biased telescopic arrangement (see Diagram 3 and 4 for example). The strength of the bias should be readily determinable by a skilled person, but should typically not be so strong that the weight of a filled container cannot compress the elongate projecting means (although of course embodiments are envisioned where manual pressure could compress the system, however in such instance further retaining means would be required to hold the container stably in place).

Preferably the temperature probe is thermally insulated from the support means and/or the elongate projecting means.

In a preferred embodiment the elongate projecting means integrally comprises a first electrical conduit connecting the temperature probe with suitable electronics for measuring and displaying, in use, the temperature of the contents of the container. This has space saving advantages in that loose wires are avoided. Alternatively, or in addition, if the elongate projecting means is longitudinally compressible by

application of the container to the device and is biased towards the concave base of the container through resilient biasing means, these biasing means could be electrically insulated from the elongate projecting means, and could integrally comprise a second electrical conduit connecting the temperature probe with suitable electronics for measuring and displaying, in use, the temperature of the contents of the container. Again this has space saving advantages in that loose wires are avoided. See for example Diagram 4 where the electrical conduits (or wires) contacting the junctions of a thermocouple are 1) the elongate projecting means (preferably telescopic) and 2) the resilient biasing means themselves. In such case the electrical conduits should be made from the same first and second metals as the first and second metals to which they are electrically attached in the thermocouple, respectively, said metals being optionally selected from copper and constantan (or other suitable pairs of metals such as nickel and nickel/chromium alloy).

Preferably the device of the invention is arranged such that in use the container is placed vertically on the support means, wherein gravity allows the perimeter of the base of the container to contact the contacting portion of the support means. Alternatively the device may be arranged such that in use the container is placed horizontally on the support means, wherein the device further comprises retaining means for keeping the perimeter of the base of the container in contact with the contacting portion of the support means. Such a retaining means may constitute a simple collar around the neck of a wine bottle for maintaining the base of the bottle in contact with the support means. Horizontal placement of bottles in a device of the invention may be advantageous where the device is present in a freezer, for instance, where horizontal placement of bottles is most convenient.

The device of the invention may be typically used for externally estimating the temperature of the liquid contents of a bottle, such as a wine bottle. The device of the invention may be free standing such that it can be moved from one environment to another (or simply used at room temperature). This has the advantage that the device may be easily cleaned, and that it may be integrated into means for transporting containers such as wine bottles. The device may also be integrated within a machine that can cool or warm the liquid contents of a container. For instance, the device is

preferably fitted to a cooled incubator (such as a fridge or freezer), or heated incubator. White wines will typically need cooling from room temperature to their appropriate serving temperature range (encompassed within the range 4-14 degrees Celsius). Red wines will typically require warming from cellar temperature (around 10 degrees Celsius) [as will certain white wines] to their appropriate serving temperature range (encompassed within the range 10-18 degrees Celsius). A comprehensive list of optimal serving wine temperature ranges could be provided with the device of the invention – either on a card or fridge magnet, or even programed into memory within the device which could be selected manually or through a remote control.

A method of externally estimating the temperature of the liquid contents of a container is further provided by this invention comprising the steps of placing a container comprising liquid contents onto the device of the invention or onto the device of the invention fitted to a fridge, freezer, or heated incubator, and measuring the estimated temperature. Furthermore, there is provided a method of decreasing the temperature of the liquid contents of a container to a particular temperature at or above the ambient temperature of a fridge or freezer (or cooled incubator) comprising the steps of placing the container onto the device of the invention fitted in a fridge or freezer (or cooled incubator), measuring the decrease of temperature in the liquid contents of the container, and removing the container from the fridge or freezer (or cooled incubator) when the particular temperature has been reached. Last, the inventor provides a method of increasing the temperature of the liquid contents of a container to a particular temperature at or below the ambient temperature of a heated incubator comprising the steps of placing the container onto the device of the invention fitted in a heated incubator, measuring the increase of temperature in the liquid contents of the container, and removing the container from the heated incubator when the particular temperature has been reached.

A method of externally measuring the temperature of the liquid contents of a container with a concave base is also provided comprising the steps of inserting a temperature probe into the space within the concave base of the container and measuring the temperature as an estimation of the temperature of the liquid contents

of the container. Preferably the temperature probe is a thermocouple, a thermistor or a resistance thermometer. Preferably the temperature probe is inserted into the space within the concave base of the container to an extent that it makes thermal contact with the surface of the container. In addition, it is preferable if the method further comprises the step of thermally enclosing (or insulating) the space within the concave base of the container from the ambient temperature of the system (external to the space).

Although all the previous embodiments have been focused on the advantageous use of the base of the container to estimate the internal content temperature, other embodiments using the principles of the above invention may be envisaged. For instance, the device of the invention could measure the temperature at the side (or any surface) of a filled container (or bottle) without being affected by the ambient temperature surrounding the container if the device comprises a temperature probe (as described above) which in use is in thermal contact with the container, but the probe, in addition, is thermally insulated from the ambient external temperature. This may be done by having an insulated cup around the probe with contacting edges that contact the container around the cup rim's perimeter thus thermally insulating the system but allowing the probe to make contact with the external surface of the container within the system. The temperature, or change of temperature may be relayed to the user as described above. Thus a device for externally estimating the temperature of the liquid contents of a container is also provided comprising a temperature probe (connected to a suitable system for displaying the estimated temperature of the liquid contents within the container) and thermal insulating means (preferably made of flexible rubber) surrounding said probe comprising a contacting surface, which is arranged so that, in use, a container's external surface may be positioned in thermal contact with the temperature probe and also making contact with the contacting surface of the thermal insulating means such that the temperature probe is thermally insulated from the ambient temperature external to the thermal insulating means. The space between the container's external surface and the thermal insulating means (containing the temperature probe) is thus insulated from the external ambient temperature. A retaining means (such as a sprung Jubilee clip) may optionally be added to the above device to maintain the container in thermal contact

with the temperature probe and in contact with the thermal insulating means (the temperature probe and thermal insulating means may be fitted within (but thermally insulated from) such retaining means). Cooling incubators (fridges/freezers) and warming incubators fitted with the above device are further provided, as are methods  
5 of using the above device in estimating the temperature (or change in temperature) of the liquid contents of the container.

Clearly devices measuring the temperature at the concave base of containers are preferred, however, as they advantageously allow a wider range of differently-  
10 shaped containers to be readily fitted in the device given the flat external base perimeter of most containers. Also the external surface of the container at the base may be more readily thermally isolated from the rest of the container (exposed to ambient temperature conditions) than other areas of the container's external surface.

15 The invention will now be described in greater detail, by way of illustration only, with reference to the accompanying (not to scale) diagrams, wherein:

**Diagram 1** is a schematic representation of the concave base of bottle thermometer showing the principle parts consisting of a base plate, which is shown as  
20 a cylinder but could be of any suitable shape, a compression spring set into the base plate, a probe head complete with a thermocouple, vanes in the "in use" position (as if a bottle were placed on the device) and a probe head to spring connector. The probe head is metallic so as to have high thermal conductivity and needs to be elastic in order to maintain good thermal contact with the apex of the cone at the base of the  
25 bottle. The spring and thermocouple should be of low thermal conductivity in so far as this is consistent with their roles. The spring-probe head connector, the spring guide and the base plate are good thermal insulators.

**Diagram 2** consists of three parts

- 30 i) an exploded view of the different component parts listed in Diagram 1  
ii) a plan view of the probe head and



- iii) a plan view of the base plate showing the use of an O-ring which needs to be a good thermal insulator and relatively narrow to reduce the thermal flow into the base plate.
- 

5        **Diagram 3** shows an alternative design for the base of bottle thermometer and consists of three parts,

- i) a top view or plan view of the thermometer head
  - ii) an equatorial cross-sectional side view of the device and
  - iii) an equatorial cross-sectional side view of the device loaded with a bottle
- 10    and showing the compression of the seals, the flexing of the vanes of the probe head and the spring loaded telescopic action of the device.
- 

15        **Diagram 4** is a preferred option which shows an equatorial cross-sectional view of the device which is a spring loaded telescope which doubles up as a thermocouple. Copper vanes (not shown) would be preferred. At least a part of the external telescope would need to be continuous copper up to the junction. The spring is made of the second material making up the thermocouple. The thermoelectric properties of spring steel (in the spring) with copper (in the telescope) could be examined. Nickel and/or Nickel/Chromium alloy could replace either or both.

20

**Diagram 5** is a schematic representation of a thermometer head in vane shape as before but incorporating a resistor formed by a long thin wire. The external connections are not shown. This device would perhaps need to be encapsulated in some protective material. This probe head would be interchangeable with the thermocouple shown in Diagrams 1,2 and 3.

25

## Examples of the potential use of the base of bottle electronic wine thermometer.

1 Free standing battery operated device for use in the door of a fridge as in Diagrams 1, 2, 3 and 4.

5

The device is portable so that it can be taken to the table with a chilled bottle. The temperature is shown on a digital display. An alarm built into the device indicates when the set temperature has been reached.

10 2 Idem but the device is built into the fridge and is supplied by an internal rectified dc supply voltage. In addition, the temperature display system and the alarm are mounted externally on the fridge door housing.

In use the wine bottle is placed vertically onto the device in the fridge door and presses down onto the probe which is maintained in good thermal contact with the top of the cone of the base by means of a spring and the elastic nature of the probe head. The probe head consists of a thermocouple or other temperature sensing device embedded in a sheet of phosphor bronze cut in a vane like shape as shown in diagram 2. The phosphor bronze is flexible and hinged such that it will fold down under the weight of the bottle but maintain contact with the bottle. It has good thermal conductivity, being metallic and will assist in achieving an accurate reading of the temperature of the base of the bottle.

25 The bottle sits on an O ring of good elasticity (Diagram 2 and 3) such as the rubber used for vacuum stoppers or washing machine seals. A partial seal is therefore formed by the action of the weight of the bottle on the O ring. The O ring is embedded in a thermally and electrically insulating base plate which serves to accommodate the spring loaded thermometer probe. The base plate is large enough to accommodate bottles up to and including Champagne bottles. The diameters of the O rings correspond to the roughened areas at the bottom of the respective bottles. The spring constant may be of the order of 3-4N/cm.

30 Flexible electrical connections from the probe are led through the spring or pass by the spring and through the base plate to a display unit containing the electronics as in the Minimum Surface Thermometer manufactured by Testo. The device starts at the ambient temperature of the fridge door but warms up at first when

4 a bottle is placed on it and then cools as the fridge cools the bottle and contents. The air at the top of the air space rapidly attains the temperature of the bottom of the bottle, while the higher density cold air from the fridge will sit just above the base plate.

5

3 Free standing battery operated device [as in Diagrams 1, 2, 3 or 4] for use in monitoring the temperature of a bottle taken from a cellar at say 10°C as it warms up. As with the previous devices this is also equipped with an indicator of when a preset temperature has been reached. This device may operate in a room temperature environment or in a heated incubator.

10

~~In the first two examples an initial transient occurs which results in the device~~  
warming at first when a bottle is placed on it. It then indicates a falling temperature as the fridge cools the bottle and its contents. In the third example the opposite is  
15 observed. The device starts at room temperature and then cools initially when the bottle is placed on it. Thereafter, it indicates a rising temperature as the bottle and contents warm up.

All of these devices are activated by means of a pressure switch within the base plate  
20 when a bottle is placed on the plate.

Preliminary experiments for the third device suggest that there is a good correlation between the temperature measured externally at the base of a wine bottle and the temperature of the contents of the bottle in the range 10-17 °C. This effect is likely to  
25 be similar for device 1 and 2. After about 20 minutes the initial transient was found to be over, and a reliable estimate of the temperature of the internal bottle contents could be measured. The initial transient time is insignificant considering that it usually takes about 2 hours to warm a cellared bottle of Bordeaux wine at 10 °C to 17 °C in a room temperature of 20 °C.

30

## Claims

1. A device for externally estimating the temperature of the liquid contents of a container with a concave base, comprising a support means with at least one  
5 contacting portion for contacting the perimeter of the base of said container, a temperature probe which is positioned within the support means such that in use the probe may measure the temperature within the space enclosed by the concave base of the container and the support means, and a suitable system for displaying the estimated temperature of the liquid contents within the container.
- 10 2. The device of claim 1, wherein the contacting portion of the support means is capable of contacting the entire perimeter of the base of the container such that the space between concave base of the container and the support means is thermally enclosed.
- 15 3. The device of claim 2, wherein the contacting portion of the support means is made of an insulating deformable material.
- 20 4. The device of claim 3, wherein the contacting portion forms a raised ridge projecting from the support means such that it may deform around and make contact with any uneven surface on the perimeter of the base of the container.
- 25 5. The device of claim 4, comprising 2 or more concentric contacting portions suitable for contacting base perimeters of various sizes of container.
6. The device of claims 1-5, wherein the support means comprises a guide portion for guiding the placement of the base of the container onto the contacting portion of the support means.
- 30 7. The device of claims 1-6, wherein the temperature probe is connected to suitable electronics for measuring and displaying, in use, the approximate temperature of the liquid contents of the container.

8. The device of claims 1-7, wherein the temperature probe is a thermocouple comprising a first and a second metal.

9. The device of claim 8, wherein the first metal is copper and the second metal is constantan.

10. The device of claims 1-9, wherein the temperature probe in use projects from the support means into the space enclosed by the concave base of the container and the support means.

11. The device of claim 10, wherein the temperature probe in use projects from the support means through an elongate projecting means.

12. The device of claim 11, wherein the elongate projecting means is positioned such that, in use, it projects the temperature probe towards the centre of the concave base of the container.

13. The device of claims 10-12, wherein the temperature probe is positioned such that in use it is in thermal contact with the surface of the concave base of the container.

14. The device of claim 13, wherein the temperature probe in use is in thermal contact with the surface of the concave base of the container through at least one flexible extension made of a material with good thermal conductivity and extending laterally from the temperature probe.

15. The device of claim 14, wherein the flexible extension is made of a resilient sheet of metal, optionally phosphor bronze or copper.

16. The device of claims 11-15, wherein the elongate projecting means is longitudinally compressible by application of the container to the device.

17. The device of claim 16, wherein the elongate projecting means is capable of compressing to the level of or below the exterior surface of the support means which,

in use, defines the space enclosed by the concave base of the container and the support means.

18. The device of claim 16 or 17, wherein the elongate projecting means is  
5 telescopically arranged.

19. The device of claims 16-18, wherein, in use, the elongate projecting means is resiliently biased towards the concave base of the container.

10 20. The device of claims 11-19, wherein the temperature probe is thermally insulated from the elongate projecting means.

21. The device of claims 11-20, wherein the elongate projecting means integrally comprises a first electrical conduit connecting the temperature probe with suitable  
15 electronics for measuring and displaying, in use, the temperature of the contents of the container.

22. The device of claim 21, wherein the elongate projecting means is longitudinally compressible by application of the container to the device and is biased towards the  
20 concave base of the container through resilient biasing means which is electrically insulated from the elongate projecting means, and wherein said resilient biasing means integrally comprises a second electrical conduit connecting the temperature probe with suitable electronics for measuring and displaying, in use, the temperature of the contents of the container.

25

23. The device of claim 22, wherein the temperature probe is a thermocouple comprising a first and a second metal, being in electrical contact with first and second electrical conduits which are made of the same respective metals, said metals being optionally selected from copper and constantan.

30

24. The device of claims 1-23, wherein it is arranged such that in use the container is placed vertically on the support means, wherein gravity allows the perimeter of the base of the container to contact the contacting portion of the support means.

25. The device of claims 1-23, wherein it is arranged such that in use the container is placed horizontally on the support means, wherein the device further comprises retaining means for keeping the perimeter of the base of the container in contact with the contacting portion of the support means.

26. The device of claims 1-25 suitable for externally estimating the temperature of the liquid contents of a bottle, such as a wine bottle.

27. A fridge, freezer, or heated incubator fitted with the device of claims 1-26.

28. A method of externally estimating the temperature of the liquid contents of a container comprising the steps of placing a container comprising liquid contents onto the device of claims 1-25 or onto the device fitted to a fridge, freezer, or heated incubator of claim 27, and reading the estimated temperature.

29. A method of decreasing the temperature of the liquid contents of a container to a particular temperature at or above the ambient temperature of a fridge or freezer comprising the steps of placing the container onto the device fitted in the fridge or freezer of claim 27, measuring the decrease of temperature in the liquid contents of the container, and removing the container from the fridge or freezer when the particular temperature has been reached.

30. A method of increasing the temperature of the liquid contents of a container to a particular temperature at or below the ambient temperature of a heated incubator comprising the steps of placing the container onto the device fitted in the heated incubator of claim 27, measuring the increase of temperature in the liquid contents of the container, and removing the container from the heated incubator when the particular temperature has been reached.

31. A method of externally measuring the temperature of the liquid contents of a container with a concave base comprising the steps of inserting a temperature probe

into the space within the concave base of the container and measuring the temperature as an estimation of the temperature of the liquid contents of the container.

5 32. The method of claim 31, wherein the temperature probe is a thermocouple, a resistance thermometer or a thermistor.

10 33. The method of claim 31 or 32, wherein the temperature probe is inserted into the space within the concave base to an extent that it makes thermal contact with the surface of the container.

34. The method of claims 31-33, further comprising the step of thermally enclosing the space within the concave base of the container.

15 35. The method of claims 31-34, wherein the temperature measurement is made when the container is present within a fridge, freezer or heated incubator which has a different ambient temperature to the liquid contents of the container.

36. The method of claim 35, wherein several temperature measurements are made to follow the change of temperature of the liquid contents of the container over time.

20 37. A device, fridge, freezer or heated incubator, constructed and arranged substantially as herein described, with reference to and as illustrated in the accompanying drawings.

25 38. A device, fridge, freezer or heated incubator according to any one of claims 1 to 27, substantially as hereinbefore described, with reference to the accompanying drawings.




## ABSTRACT

---

### 5 Thermometer

The present invention relates to the field of thermometers for measuring the temperature of the liquid contents of containers. It is undesirable to open the container (such as a wine bottle) to measure the temperature of its liquid contents. Nevertheless,  
10 it is otherwise problematic to follow the temperature change in a container placed in either a cooling or heating incubator. The present invention provides a device for externally estimating the temperature of the liquid contents of a container with a concave base (particularly wine bottles), comprising a support means with contacting portions for contacting the perimeter of the base of said container, a temperature  
15 probe positioned within the support means such that in use the probe may measure the temperature within the space enclosed by the concave base of the container and the support means, and a system for displaying the estimated temperature of the container's liquid and/or indicating when the desired temperature has been reached.

DIAGRAM 1 : SCHEMATIC REPRESENTATION OF BASE OF BOTTLE THERMOMETER



NOT SHOWN :

O' RINGS SEALS

THERMOCOUPLE WIRES

DISPLAY UNIT

NOT TO SCALE.

EXPLODED EQUATORIAL CROSS SECTIONAL VIEW

DIAGRAM 2


19.1.03

PROBE HEAD




PROBE HEAD CONTAINS  
THERMOCOUPLE OR OTHER  
TEMPERATURE READING  
DEVICE. WIRES NOT SHOWN.


PLAN VIEW PROBE HEAD




SPRING- PROBE HEAD  
CONNECTOR




3. SPRING



PLAN VIEW BASE PLATE




4. SPRING GUIDE



SEAL

CONNECTION

CHANNELS  
LINKING PROBE  
HEAD TO DISPLAY




5. BASE  
PLATE

# DIAGRAM 3

## ALTERNATIVE DESIGN FOR BASE OF BOTTLE THERMOMETER


TOP VIEW  
THERMOMETER HEAD



COPPER or  
PHOSPHOR BRONZE

THERMOCOUPLE

EQUATORIAL  
CROSS-SECTIONAL  
SIDE VIEW OF  
DEVICE



EQUATORIAL  
CROSS-SECTIONAL  
SIDE VIEW : DEVICE LOADED  
WITH A BOTTLE





Diagram 4: Combined Thermocouple/Spring Loaded System



## RESISTANCE THERMOMETER HEAD

- external connections not shown
- thin, etched <sup>other</sup> Cu/ wire on a flexible substrate
- probably needs to be encapsulated in some durable material.




DIAGRAM 5

PCT/GB2004/001620



This Page is inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ BLACK BORDERS
- ☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☒ COLORED OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REPERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images  
problems checked, please do not report the  
problems to the IFW Image Problem Mailbox**